

## Introduction:

ALICON MACH4T 20W-40 API SL JASO MA2 is unique premium lubricant blended with superior high viscosity index base oil & versatile additive technology. Recommended for 4 stroke engines of modern motorcycles. Specially designed and formulated to ensure longer life of engines, clutch & gear components. This Oil meets (VTW) valve train wear of API SL of SAE 20W-40.

## Applications:

- All new generation 4 stroke two wheeler engine of reputed OEMs.
- Recommended for 4 stroke two wheelers like Hero Honda, Bajaj Auto, TVS, Yamaha, Kinetic, LML, Honda, etc.

## Advantages:

- Highly shear stable.
- Lower high temperature deposits
- Lower oil consumption
- Prevents clutch slippage at varying speeds
- Catalytic convertor compatible

## Performance Standard:

API SL , JASO MA2

## Typical Specifications:

Sr. No.	Characteristics	Test Method	Typ. Value
1	Appearance	VISUAL	Bright & Clear
2	Colour, Max	ASTM D 1500	3
3	Kinematic Viscosity at 100 C, cSt	ASTM D - 445	13.5-15.5
4	Viscosity Index, Min	ASTM D - 2270	110
5	TBN, mg KOH/g	ASTM D - 2896	5 - 7
6	Flash Point, (COC), C Min	ASTM D - 92	210
7	Pour Point, C Max	ASTM D - 97	(-)21

## Environment, Health & Safety:

Every care has been taken to ensure the accuracy of the information in this PDS. This however may be affected by subsequent improvement in product (R&D). MSDS is available for all ALICON products on request.

ALICON products are unlikely to present any health and safety hazard with proper use for the correct application and maintain proper personal hygiene. Do not Spill oils on the shop floor, discharge into drains ,ground or water sources.