

## CIRCULATING & HYDRAULIC OIL (ALICON HYFLOW WW- 32/46/68/100(WATER WHITE)

#### Introduction:

ALICON HYFLOW WW grades are blended from highly refined base stock and carefully selected anti-oxidant, anti-wear, anti-rust and anti-foam additives to meet the requirement of high pressure systems and also where pumps of high speed are operated.

### **Applications:**

Alicon Hyflow WW grades are effective in reducing vane, piston & gear pump wear and so recommended for use in hydraulic systems, enclosed gear box, chain drives, compressors, vacuum pumps, mining machinery, machine tools, oil circulating systems. Also used in antifriction bearings of electricmotors.

#### **Advantages:**

- Tailor made viscosity to suit hydraulic systems.
- Good film strength
- Excellent anti-wear properties.
- Good demulsibility characteristic.
- Anti corrosive
- Good anti rusting and oxidation stability.
- Excellent anti foaming

#### **Performance Standard:**

Meets IS - 10522 - 1983 , Vickers V- 104 C , DIN:51524 Part 1(H&HL), US Steel 126

Sr. No	Characteristics	Test Methods	32	46	68	100
	Product Code	0	IND/20	IND/21	IND/22	IND/23
1	Appearance	Visual	Clear liquid	Clear liquid	Clear liquid	Clear liquid
2	Colour, Max	<b>ASTM D 1500</b>	1	1	1	1
3	Kinematic Viscosity at 40 oC, cS	ASTM D 445	<b>29-</b> 35	41-50	61-75	90-110
4	Viscosity Index, Min	<b>ASTM D 2270</b>	100	100	100	110
5	Flash point, oC Min	ASTM D 92	180	190	200	210
6	Pour Point, oC Max	ASTM D 97	-12	-15	-18	-21
7	Copper strip corrosion at 100 o ( for 3 Hrs	C ASTM D 130	1A	14	<b>1A</b>	1 <b>A</b>

#### **Typical Specifications:**

#### Environment, Health & Safety:

Every care has been taken to ensure the accuracy of the information in this PDS. This however may be affected by subsequent improvement in product (R&D). MSDS is available for all ALICON products on request.

ALICON products are unlikely to present any health and safety hazard with proper use for the correct application and maintain proper personal hygiene. Do not Spill oils on the shop floor, discharge into drains ,ground or water sources.

# Alicon Petroleum & Rubber Products Pvt. Ltd.

Regd Office: 206/207 Vinayak Commercial complex manjalpur Vadodara-390011, Gujarat E-mail: info@alicon.in Website: www.alicon.in